

NAVVIS

Physical

Design	Wearable
Dimensions (H x W x L)	108 × 33 × 56 cm
Weight	9.3kg
Housing	Anodized aluminum

Operation

Battery	2 × 2 Li-ion V-Mount Micro, hot swappable
Operating time	1.5 hours (with 1 set of 2 bat- teries)
Memory	1TB removable
Sensors	WiFi, Bluetooth, IMU

Laser Scanners

Number of laser scanners	2 × 16-layer
Laser class	1, eye-safe per IEC 60825-1:2007 & 2014
Wavelength	903nm
Field of View (FOV)	360° horizontal, 360° vertical
Range	Max. 100m
Points per second	2 × 300,000

Cameras

Number of cameras	4
Image resolution	4 × 20 megapixel
Focus	Fixed
Lens	Fisheye, 3.3mm, aperture f/2.4

*Environment dependent: Measured in a room of 100m². All accuracy statements are one sigma.

Accuracy

Relative accuracy of point cloud*	8mm
Control point support	Ground and wall

Output

Images	JPEG
Point cloud	E57, LAS, PTS, XYZ, PLY

Environment

Operating temperature	5°C to 35°C, non-condensing
Robustness	Indoors and building surroundings

Display

Туре	AMOLED
Dimensions	5.5"
Resolution	1080 × 1920
Touch technology	Capacitive multi-touch

Transport Case

Dimensions (H × W × L)	47 x 51 x 78cm
Weight (fully equipped)	26.8kg